

2500 E

Specifications



Type	2500 E	2500 EB	2500 EBD
Max. working height	25.10 m	25.10 m	25.10 m
Max. outreach	12.60 m	12.60 m	12.60 m
Basket size	1.25x 0.8x1.1 m	1.25x0.8x1.1 m	1.25x0.8x1.1 m
Travelling length	8.40 m	8.40 m	8.40 m
Travelling height	2.10 m	2.10 m	2.10 m
Travelling width	1.70 m	1.70 m	1.70 m
Operational width	4.25 m	4.25 m	4.25 m
Power supply	230 V 16 A		
Battery		24 V 200 Ah/5h	24 V 200 Ah/5h
Charger		24 V 30 A	24 V 30 A
Generator			24 V 22 A
Turntable basket ±	41°	41°	41°
Rotation ±	400°	400°	400°
Max. basket load	200 kg	200 kg	200 kg
Total weight incl. propulsion	3000 kg	3060 kg	3180 kg
Diesel motor			14 kW 18.8 hp

Automatic stabilizer levelling system up and down	O
Diesel engine with oil pump	O
Flash lights	O
Hatz diesel engine with oil pump	O
Holder for nose wheel	O
Hour meter	O
Petrol engine with oil pump	O
Plates for stabilizers	O
Special colour 2500 E	O
Spotlight in basket O16	O
Swing-up control panel	O
Transformer	O

O Option

OMMELIFT



2500 E

