# S2632E/2646E/3246E

SLAB SCISSOR LIFTS



- Self-propelled electric scissor lifts
- Compact and robust
- Roll-out extension decks for extra reach
- 1.16m wide models rated for outdoor use
- Ideal for construction and maintenance applications




## SLAB SCISSOR LIFTS \$2632E/2646E/3246E

DIMENSIONS	S2632E	S2646E	\$3246E
Max. working height	10.0m	10.0m	11.8m
Max. platform height (A)	8.0m	8.0m	9.75m
Platform size (stowed)	0.74m x 2.31m	1.14m x 2.38m	1.14m x 2.38m
Platform size (extended)	0.74m x 3.22m	1.14m x 3.30m	1.14m x 3.30m
Deck extension length (B)	0.91m	0.91m	0.91m
Overall width (C)	0.81m	1.16m	1.16m
Stowed length (D)	2.37m	2.54m	2.54m
Stowed height (E)	2.33m	2.36m	2.51m
Stowed height (guardrails folded)	1.93m	1.67m	1.82m
Wheelbase	1.92m	1.9m	1.9m
Ground clearance (stowed)	63mm	101mm	101mm
Ground clearance (elevated)	19mm	25mm	25mm

PERFORMANCE				
Platform capacity (SWL)	227kg	454kg	317kg	
Max. operating wind speed (1 person on platform)	0m/s	12.5m/s	12.5m/s	
Max. drive height	8.0m	7.90m	9.75m	
Max. drive speed (elevated)	0.6km/h	0.8km/h	0.8km/h	
Max. drive speed (stowed)	3.2km/h	3.2km/h	3.2km/h	
Raise/lower time	20/26sec	35/60sec	50/60sec	
Gradeability	25%	25%	25%	
Inside turning radius	0.25m	0.25m	0.25m	
Outside turning radius	2.34m	2.5m	2.5m	
Tyres	38.1cm x 12.7cm non-marking solid rubber			
Controls	one-hand proportional joystick			
Drive system	dual front wheel hydraulic motors			

POWER	
Power source	24V 4hp DC electric motor 4 x 6V 240 Ah batteries

WEIGHT			
Gross weight	2,224kg	2,359kg	3,003kg




### STANDARD FEATURES

- Proportional controls
- 0.9m extension deck
- Tilt alarm
- Swing-out service trays
- Approved for outdoor use with one person on platform (S2646E/S3246E)
- Power line to platform (no sockets)
- Horn
- Hour meter
- CE approved

### **OPTIONS**

- Special paint colours
- Flashing amber beacon
- Airline to platform
- Dual lanyard anchorage points

#### TURNING RADIUS



## **S**snorkel

Vigo Centre, Birtley Road, Washington, Tyne & Wear,

e: sales@snorkellifts.com