



Scissors Access Platforms

DIMENSIONS	S1930	S2033
Max. working height	7.8m	8m
Max. platform height (A)	5.8m	6.1m
Platform size (stowed)	2.39m x 0.76m	2.14m x 1.09m
Platform size (extended)	3.3m x 0.74m	3.36m x 1.09m
Deck extension length (B)	0.91m	0.91m
Overall length (D)	2.3m	2.3m
Overall width (C)	0.81m	1.17m
Stowed height (E)	2.14m	2.01m
Min. height (guardrails folded)	1.73m	1.66m
Ground clearance (stowed)	95mm	95mm
Ground clearance (elevated)	19mm	19mm

Platform capacity	227kg	340kg
Max. drive height	7.9m	7.9m
Max. drive speed (elevated)	3.2km/h	3.2km/h
Max. drive speed (stowed)	0.6km/h	0.6km/h
Gradeability	25%	25%
Inside turning radius	0.76m	0.53m
Outside turning radius	2.36m	2.41m
Tires	0.38m x 0.1m non-marking rubber	0.38m x 0.13m non-marking rubber
Controls	proportional	proportional
Drive system	2 wheel drive	2 wheel drive

POWER	
Power source	4 x 6V 240amp hour batteries
Charger	90-240V 25amp

WEIGHT

Gross weight

1650kg

2035kg

